

Instructions for maintaining solvent quality with PURITAN® All-Carbon Cartridges

Excessive dye in the solvent is a leading cause of garment graying and unhappy customers.

Rely on the PURITAN All-Carbon Cartridge for the clean solvent performance you need.

**Spent cartridges containing solvents classified as hazardous should be handled as hazardous waste and disposed of in accordance with applicable federal, state and local regulations governing waste disposal.*

When to Change PURITAN All-Carbon Cartridges

Solvent flow rate is the best method for determining when to change cartridges. Replace cartridges when fill time through the filter exceeds 1.5 minutes to reach working level, or when solvent color cannot be maintained at an acceptable level. PURITAN All-Carbon Cartridges should be changed at the same time Carbon-Core Cartridges are changed.

How to Change Spent PURITAN All-Carbon Cartridges

1. Follow filter system manufacturer's instructions for solvent recovery from spent cartridges. Allow cartridges to drain at least 24 hours. *CAUTION: Check the solvent storage capacity of your drycleaning system before draining filters.*
2. Before removing spent cartridges from their housing, consult the solvent SDS for safe handling information.
3. Remove spent cartridges and felt gaskets from the housing. As spent cartridges will retain residual amounts of solvent, care must be taken to prevent spilling or dripping solvent. Handle in accordance with all federal, state and local regulations governing disposal.*
4. Refill housings with new PURITAN All-Carbon Cartridges and the proper cartridge felt gaskets. *Be sure that all felt gaskets are secured in place to prevent soil bypass and all housing gaskets are properly fitted to prevent leakage.*
5. Reinstall cover(s) and check all valves for proper setting. Close all drain valves and air vents.
6. Fill filter and circulate, bleeding air vent lines until filter is liquid full.
7. Circulate solvent through the filters for 15 minutes or until the sight glass clears, whichever occurs last.
8. Clean 2 or 3 dark loads before cleaning a light or white load.

How to Obtain Maximum Cartridge Life

1. Follow filter manufacturer's operating instructions.
2. If possible, turn off all-carbon solvent flow until about half of the carbon-core cartridge life is used. Bleed air out of the all-carbon housing each day to keep it liquid full.
3. When half of the expected carbon-core cartridge life has been used, open the carbon flow control valve and circulate until the solvent clears. Run several dark loads before cleaning light loads.
4. Use all-carbon cartridges only in housings designed for them. They should never be placed where carbon-core cartridges are normally used.
5. Be certain that all gaskets for the carbon-core cartridges are in good shape and installed properly. Bypass of particulate soil will plug the all-carbon shell and center tube. When this happens, the all-carbon cartridge outer shell will rupture and release carbon into the housing. However, the intact PURITAN center tube will prevent carbon loss to the cleaning machine in most filters.
6. The use of all-carbon cartridges after a powder filter is not recommended. Most powder filters leak insoluble soil and plug the all-carbon cartridges.
7. Distill a minimum of 5 gallons per 100 lbs. of cleaning.
8. Bleed filter housing(s) daily.

How to Order PURITAN All-Carbon Cartridges

PURITAN All-Carbon Cartridges and gaskets are sold by authorized Street's distributors everywhere. Order PURITAN All-Carbon cartridges in cases of four.

For professional drycleaning use only.

Advancing the Technology of Clean™