

Instructions for Using STEAM DRAGON™

STEAM DRAGON
sequesters and
removes minerals
dissolved in water.

STEAM DRAGON
also removes
potentially harmful
dissolved oxygen from
the boiler and works
to neutralize corrosive
carbonic acid.

For Daily Maintenance To Prevent Scale Build-Up

Daily use of this product and following boiler manufacturers recommendations for blow down and maintenance can result in maximum boiler life and efficiency.

Add STEAM DRAGON directly into the boiler feed or return system. Follow recommended established addition rate and factory recommended blow-down procedures. Variations in dosage might be needed to compensate for varying local water conditions.

Check water condition with Water Monitor™ Test Kit every week for the first 30 days and adjust additions thereafter accordingly.

STEAM DRAGON is designed to be used in boilers that have been under a regular water treatment and water monitoring program. Caution must be used whenever a water treatment is introduced into a boiler that has been in operation for some time with no treatment, as there is a possibility that loosened scale and rust could cause system problems such as clogged steam traps and contamination of steam. In all cases, STEAM DRAGON needs to be used in accordance with STEAM DRAGON usage instructions and the boiler manufacturer's recommended preventative maintenance procedures.

Boiler Horse Power	Daily Dose of STEAM DRAGON
5 HP or less	3 OZ.
6 - 8 HP	4 OZ.
9-12 HP	6 OZ.
13-16 HP	8 OZ.
17-20 HP	10 OZ.
21-24 HP	12 OZ.
25-28 HP	14 OZ.
29-32 HP	16 OZ.

How to Order STEAM DRAGON

STEAM DRAGON is sold by authorized Street's distributors everywhere. STEAM DRAGON is available in single one-gallon containers, cases of four gallons, 5-gallon pails and 15-gallon drums.

Before using any chemical product, review the Safety Data Sheet (SDS) for safe handling and proper disposal.

For professional drycleaning use only.

Advancing the Technology of Clean™